



MTN Inspirations LX

POU Cooler

501-BMTNILX

Black Cold/Room Temp

502-BMTNILX

Black Hot/Cold Temp

501-WMTNILX

White Cold/Room Temp

502-WMTNILX

White Hot/Cold Temp

Power

Voltage	115, 220, 100
Frequency (Hz)	50/60
Power Consumption	4.89A / 554W / 115V
Cold Power Consumption	1.42A / 118W / 115V
Hot Power Consumption	3.87A / 449W / 115V
ES (kWh/24 hrs.)	0.81
% lower than ES Standard	0.07

Hot Water System

Avg. Hot Water Temp at Nozzle @77°F Ambient (Before/After On)	166.57°F / 191.43°F
Hot Water ARI Rating	45, 6 oz > 165°F +/- 10%
Hot Thermometer / Heat Limiter	203°F +/- 5.5°F
Hot Thermostat / Thermister Cycle	167°F +/- 11°F
Hot Water Flow Rate	0.96 oz/sec
Hot Tank Size (Liter : Gallon)	2.0L : .53G
Heat Band Wattage	450W

Cold Water System

Avg. Cold Water Temp at Nozzle @ 75°F ambient (Before/After ON)	45.87°F / 42.2°F
Cold Water ARI Rating	27, 5 oz < 50°F +/- 10%
Cold Thermostat Set Point	45°F + 3°/-8°F
Cold Water Flow Rate	1.4 oz/sec
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter : Gal)	78 / 2.08 / 1.51 : 1 / 0.55 / 0.4

Weights and Measurements

Net Weight (H&C / C&C Lbs)	34.6 / 31.68
Gross Weight (H&C / C&C Lbs)	37.9 / 34.98
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	12.4x13.5x39 / 13x13.9x40
Container Load (20')	224
Container Load (40')	462
Container Load (40' HC)	462
Container Load (45" HC)	518
Certifications	UL Listed