



502-SSART

Stainless Steel Hot/Cold Temp

Artesian POU Cooler

Power	
Voltage	115V
Frequency (Hz)	60 Hz
Power Consumption	5.42A / 601W / 110V
Cold Power Consumption	1.43A / 117W / 110V
Hot Power Consumption	4.32A / 500W / 110V
ES (kWh/24 hrs.)	0.80
% lower than ES Standard	6%

Hot Water System	
Avg. Hot Water Temp at Nozzle @ 75°F Ambient (Before/After On)	167°F - 192.1°F
Hot Water ARI Rating	45, 6 oz > 165°F +/- 10%
Hot Thermostat / Heat Limiter	187°F - 203°F
Hot Thermostat / Thermister Cycle	167°F +/- 11°F
Hot Water Flow Rate	.67 - .74 oz/sec
Hot Tank Size (Liter : Gallon)	.54 gal
Heat Band Wattage	450W

Cold Water System	
Avg. Cold Water Temp at Nozzle @ 75°F ambient (Before/After On)	45.9°F / 42.1°F
Cold Water ARI Rating	5 oz - 6 oz < 50°F +/- 10%
Cold Thermostat Set Point	40°F +/- 10%
Cold Water Flow Rate	1.2 - 1.4 oz/sec
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Liter : Gallon)	3.8 / 2.07 / 150:1 / 0.55 / 0.4

Weights and Measurements	
Net Weight (Lbs)	40 lbs
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	12" x 12.5" x 42 7/8"
Container Load (20')	224
Container Load (40')	456
Container Load (40' HC)	456
Container Load (45" HC)	532
Certifications	UL Listed